



<p>Flame Detector Type: AH-0014</p> 	SPECIFICATION	
	Voltage Range	12 ~ 30 Volt DC
	Alarm Current	35mA (@ 24 Volt DC 470Ω)
	Standby Current	45μA
	Sensor Type	Ultraviolet
	Sensitive Angle	120°
	Sensitive Range	Detec flame of 15mm at distance of 3m
	Ambient Temperature	-10°C ~ +55°C
	Material	Fire-proof plastic
	Dimension	111mm (Dia.) x 47mm (H)
	Weigh	About 170g
	Color	White

<p>Gas Detector Type: AH-0822</p> 	SPECIFICATION	
	Power Source	24 Volt DC
	Alarm Current	75mA ~ 80mA
	Standby Current	40mA ~ 45mA
	Charging Period	About 35 seconds
	Alarm Sound	90dB/m and above
	Sensitivity	0.05 ~ 0.30%
	Detection Type	Natural Gas and Propane Gas
	Ambient Temperature	-10°C ~ +55°C
	Dimension	102mm (Dia.) x 40.5mm (H)
	Weigh	About 130g
	Color	White

<p>Fire Alarm Bell Type: AH-0218</p> 	SPECIFICATION	
	Dimension	Ø 6 Inchi / 152mm (Dia) x 56mm (H)
	Voltage	24 Volt DC
	Current	25mA
	Sound Output	93dB/1m
	Movement	Motor, pinion and striker
	Movement Features	DC motor, acetral gear wheel, steel striker
	Gong	Steel, scured with philips srcew
	Base Plate	Molded black polycarbonate
	Weigh	About 850g
	Color	Red

<p>Fire Indicating Lamp Type: AH-9719</p> 	SPECIFICATION	
	Dimension	90mm (Dia) x 70 (H)
	Consumption Current	24 Volt DC 60mA / LED 20mA
	Bulb	30V/2W with bulb or LED
	Lamp Cover	Fire-proof plastic
	Lamp Base	Fire-proof plastic
	Weigh	About 70g
	Color	Red